



Spies Hecker	SATAjet® X 5500 HVLP	SATAjet® X 5500 RP®	SATAjet® 5000 B HVLP	SATAjet® 5000 B RP®	SATAjet® 4000 B HVLP	SATAjet® 4000 B RP®
Priomat / Permacron	-	-	1.3 / 1.4 / 1.5	1.2 / 1.3 / 1.4	1.3 / 1.4 / 1.5	1.2 / 1.3 / 1.4
Elastic Haftgrund- Füller	-	-	2.0 bar	2.0 bar	2.0 bar	2.0 bar
Permasolid	-	-	1.3 / 1.4 / 1.5	1.2 / 1.3 / 1.4	1.3 / 1.4 / 1.5	1.2 / 1.3 / 1.4
Nass-in-Nass Füller- Grundierfüller	-	-	2.0 bar	2.0 bar	2.0 bar	2.0 bar
Permahyd Hi-TEC 480	1.2 l 2.0 bar	1.2 l / 1.2 O 2.0 bar	WSB / 1.3 2.0 bar	1.2 W / 1.2 / 1.3 2.0 bar	WSB / 1.3 2.0 bar	1.2 W / 1.2 / 1.3 2.0 bar
Permahyd Serie 280/285	- -	- -	WSB / 1.3 2.0 bar	1.2 W / 1.2 / 1.3 2.0 bar	WSB / 1.3 2.0 bar	1.2 W / 1.2 / 1.3 2.0 bar
Permasolid HS Klarlack 8030	- -	1.3 l / 1.3 O / 1.4 l / 1.4 O 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar
Permasolid HS Klarlack 8034	- -	1.3 l / 1.3 O / 1.4 l / 1.4 O 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar
Permasolid HS Klarlack 8035	- -	1.3 l / 1.3 O / 1.4 l / 1.4 O 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar
Permasolid HS Klarlack 8055	- -	1.3 l / 1.3 O / 1.4 l / 1.4 O 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar
Permasolid HS Optimum Plus Klarlack 8655	- -	1.3 l / 1.3 O / 1.4 l / 1.4 O 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar	- -	1.3 / 1.4 1.8 - 2.2 bar
Permasolid HS Race Clear 8700	- -	1.2 l / 1.2 O / 1.3 l / 1.3 O 1.8 - 2.0 bar	- -	1.2 / 1.3 1.8 - 2.0 bar	- -	1.2 / 1.3 1.8 - 2.0 bar
Permasolid HS Speed Klarlack 8800	- -	1.2 l / 1.2 O / 1.3 l / 1.3 O 1.8 - 2.0 bar	- -	1.2 / 1.3 1.8 - 2.0 bar	- -	1.2 / 1.3 1.8 - 2.0 bar
-	- -	- -	- -	- -	- -	- -

*Alle Angaben nach bestem Wissen und Gewissen aber ohne Gewähr. Bitte beachten Sie die Vorgaben des Lackherstellers. | Specifications in all conscience but without engagement. Please observe the paint manufacturer's requirements. |

Toutes indications sont en notre âme et conscience mais sans garantie. Veuillez respecter les instructions du fabricant de peinture. | Todos los datos según nuestro saber y entender, pero sin garantía. Tenga en cuenta las especificaciones del fabricante de pintura.



Spies Hecker	SATA [®] minijet 4400 [®] B HVLP	SATA [®] minijet 4400 [®] B RP [®]	SATAminijet [®] 3000 B HVLP	SATAjet [®] 100 B F [®] RP [®]	SATAjet [®] 100 B F [®] HVLP	SATAjet [®] 100 B P [®]
Priomat 1K / 2K Wash Primer	0.8 / 1.0 / 1.2	0.8 SR / 1.0 SR / 1.2 SR	0.8 / 1.0 / 1.2	1.4	1.4	-
	1.0 - 2.0 bar	1.0 - 2.0 bar	1.0 - 2.0 bar	1.5 - 2.2 bar	1.5 - 2.0 bar	-
Permasolid 2K HS Grundierfüller	1.0 SR / 1.2 SR / 1.4 SR	1.0 SR / 1.2 SR / 1.4 SR	1.0 SR / 1.2 SR / 1.4 SR	1.4	1.4	-
	1.0 - 2.0 bar	1.0 - 2.0 bar	1.0 - 2.0 bar	1.5 - 2.2 bar	1.5 - 2.0 bar	-
Permasolid 2K HS Füller	1.2 SR / 1.4 SR	1.2 SR	1.2 SR / 1.4 SR	1.4 / 1.6 / 1.8	1.4 / 1.7 / 1.9	-
	1.0 - 2.0 bar	1.0 - 2.0 bar	1.0 - 2.0 bar	1.5 - 2.2 bar	1.5 - 2.0 bar	-
Raderal Spritzspachtel	-	-	-	-	-	P (2.5)
	-	-	-	-	-	1.5 - 2.5 bar
Permahyd Basislack 280/285 / Hi-TEC 480	0.8 SR / 1.0 SR / 1.2 SR	0.8 SR / 1.0 SR / 1.2 SR	0.8 SR / 1.0 SR / 1.2 SR	-	-	-
	1.0 - 2.0 bar	1.0 - 2.0 bar	1.0 - 2.0 bar	-	-	-
Permasolid 2K HS Autolack / Klarlack	1.0 SR / 1.2 SR	1.0 SR / 1.2 SR	1.0 SR / 1.2 SR	-	-	-
	1.0 - 2.0 bar	1.0 - 2.0 bar	1.0 - 2.0 bar	-	-	-
-	-	-	-	-	-	-
	-	-	-	-	-	-
-	-	-	-	-	-	-
	-	-	-	-	-	-
-	-	-	-	-	-	-
	-	-	-	-	-	-
-	-	-	-	-	-	-
	-	-	-	-	-	-
-	-	-	-	-	-	-
	-	-	-	-	-	-
-	-	-	-	-	-	-
	-	-	-	-	-	-

*Alle Angaben nach bestem Wissen und Gewissen aber ohne Gewähr. Bitte beachten Sie die Vorgaben des Lackherstellers. | Specifications in all conscience but without engagement. Please observe the paint manufacturer's requirements. |
 Toutes indications sont en notre âme et conscience mais sans garantie. Veuillez respecter les instructions du fabricant de peinture. | Todos los datos según nuestro saber y entender, pero sin garantía. Tenga en cuenta las especificaciones del fabricante de pintura.